



INNOVATIONS FOR LIVING™

INSULPINK®  
Insulation

## Product Data Sheet



### Product Data

INSULPINK Insulation is an extruded polystyrene closed-cell foam panel. INSULPINK insulation is produced by Owens Corning's patented Hydrovac® process technology under conditions of strict quality control.

#### Property

Weight	Approx. 130 lb./1,000 sq. ft. for each inch of thickness.
Packaging	Shipped in units (8' high x 4' wide x 8' deep); 8 stretch-wrapped bundles per unit.
Compliance with standards	Meets building code approvals - see BOCA 2603, ICBO 2602, SBCCI 2603, ASTM C 578 Type X. Underwriters Laboratories, Inc.® See Classification Certificate U-197.

### Product Availability

#### Property

Thickness	1 1/2" (R-7.5)
Width x Length	24" x 96"
Edges	Slotted

Help reduce job site labor costs while you install premium insulation.

- Available in a thickness of 1 1/2" with slotted edges to accommodate furring.
- Provides high R-Value of 5 per inch of thickness.
- Extruded polystyrene insulation offers excellent moisture resistance for long-term thermal performance.
- Lightweight, durable rigid foam panels are easy to handle and install.

**Caution:** Combustible. Although it does contain a flame-retardant additive to inhibit ignition from small fire sources, if exposed to fire of sufficient heat and intensity, INSULPINK insulation will ignite. Do not expose the product to open flame during shipping, storage, installation or use. In most applications, a code-compliant thermal barrier must be used to separate INSULPINK insulation from the building interior. See conditions of use section of ICC ES Report 96-24 for application covering recommendations.

Grinding, sawing or fabricating can produce dust particles which may be irritating to eyes, nose and throat. Avoid buildup of dusts. Certain conditions form explosive dust atmospheres that can be ignited. Ensure adequate ventilation.

### Typical Physical Properties<sup>1</sup>

Property (units)	Test Method <sup>2</sup>	Value
Thermal conductivity - "k" (Btu x in/hr x ft <sup>2</sup> x °F max.) <sup>3</sup> @ 75°F mean temperature @ 40°F mean temperature	ASTM C 518	0.20 0.18
Thermal Resistance - R-Value per inch of thickness @ 75°F mean temperature @ 40°F mean temperature	ASTM C 518	5.0 5.4
Compressive Strength (min. lb./in <sup>2</sup> ) <sup>4</sup>	ASTM D 1621	15.0
Flexural Strength (min. lb./in <sup>2</sup> ) <sup>5</sup>	ASTM C 203	60
Water Absorption (max. % by volume) <sup>6</sup>	ASTM C 272	0.10
Water Vapor Permeance (max. perm) <sup>7</sup>	ASTM E 96	1.10
Water Affinity	—	hydrophobic
Water Capillarity	—	none
Dimensional Stability (max. % linear change) <sup>8</sup>	ASTM D 2126	2.0
Linear Coefficient of Thermal Expansion (in./in./°F max)	—	2.7 x 10 <sup>-5</sup>
Flame Spread <sup>9,10</sup>	ASTM E 84	5
Smoke Developed <sup>9,10,11</sup>	ASTM E 84	45-175
Oxygen index (min.) <sup>9</sup>	ASTM D 2863	24

<sup>1</sup>Properties shown are representative values for 1" thick material based upon most recent product quality audit data.

<sup>2</sup>Modified as required to meet ASTM C 578-92.

<sup>3</sup>Thermal resistance (R) - (hr. x ft<sup>2</sup> x °F/Btu) - of a 1" thickness 5.0 (at 75°F mean temperature), 5.4 (at 40°F mean temperature).

<sup>4</sup>Value at yield or 10% deflection, whichever occurs first.

<sup>5</sup>Value at yield or 5% deflection, whichever occurs first.

<sup>6</sup>Data ranges from 0.00 to value shown.

<sup>7</sup>Actual water vapor permeance data for 1" thick material value decreases as thickness increases.

<sup>8</sup>Data ranges from 0.0 to value shown.

<sup>9</sup>These laboratory tests are not intended to describe the hazard presented by this material under actual fire conditions.

<sup>10</sup>Data from Underwriters Laboratories, Inc.® classified. See Classification Certificate U-197.

<sup>11</sup>ASTM E 84 is thickness-dependent, therefore a range of values is given



INNOVATIONS FOR LIVING™


#### OWENS CORNING WORLD HEADQUARTERS

ONE OWENS CORNING PARKWAY

TOLEDO, OHIO 43659

1-800-GET-PINK

www.owenscorning.com



Pub. No. 45203-B. Printed in U.S.A. November 2005. THE PINK PANTHER™ & ©1964-2005 Metro-Goldwyn-Mayer Studios Inc. All Rights Reserved. The color PINK is a registered trademark of Owens Corning. ©2005 Owens Corning.